

Model: Tremblant HP741/HP741R

Description:



Curved & Fluid style CSA Type 1, ANSI Type I 1 without rain trough, ideal for mining, Steel, Construction and Heavy metal work. With universal accessory slots for a wide range of accessories. It also gives the choice between ratchet or pin-lock adjustments & nylon-webbing 4 points suspension system.

Product Number	Description	Order Multiples	Case Quantity	Case Dimensions	Case Weight
HP741	Pin-Lock, Nylon 4 point suspension	12	12	44.5 X 32 X 62.5 cm 17.5" X 12.5" X 24.5"	4.67 kg. 10.3 lbs.
HP741R	Sure-Lock Ratchet, Nylon 4 point suspension	12	12	44.5 X 32 X 62.5 cm 17.5" X 12.5" X 24.5"	4.81 kg. 10.6 lbs.

Size	N/A	COUNTRY OF ORIGIN	Canada
TYPE	CSA Type 1, ANSI Type I	MATERIALS	Shell: HDPE Suspension: HDPE/Nylon Webbing
CLASSIFICATION	Class E (dielectric)	WEIGHT	HP741: 339 g./ 0.87lbs. HP741R: 380 g./0.84 lbs.
COMPLIANCE	CSA Z94.1-15, ANSI/ISEA Z89.1-2014	THERMAL RESISTANCE	Melting Point: 500°F (260°C) Softening Temp.: 262°F (128°C)
COMPONENT CLASSIFICATION	N/A	REPLACEMENT SUSPENSION	HP741= HP241S: pin-lock HP741R= HP741RS: Ratchet
COLORS	01/White, 02/Yellow, 03/Orange, 04/Dark Green, 05/Hi-viz Red, 06/Light Blue, 07/Sky Blue, 08/Navy Blue, 09/Gray, 10/Beige, 11/Black, 15/Red, 17/Royal Blue, 31/Hi-Viz Orange, 44/Hi-Viz Yellow		

Training and Proper Use: Please refer to product manual included with the products prior to use. NOT FOLLOWING Manufacturer instructions may preclude into injury, sickness or even death.

For Additional Information: 1-877-446-3278

Revision : MAY 22-17

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374/ 1 877 446-3278
F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
T: (905) 565-9990
F: (905) 565-9906

