



WHITE KNIGHT™ FOOD GRADE ANTI-SEIZE

DESCRIPTION

WHITE KNIGHT™ is a premium quality anti-seize compound developed specifically for use in applications where incidental food contact is possible and is composed entirely of ingredients that meet NSF H1 requirements. This aluminum complex based anti-seize protects metal parts from seizure, galling, rust, corrosion and heat freeze by tenaciously adhering to the metal surface. **WHITE KNIGHT™** provides a degree of safety and protection unsurpassed by any other product.

- NSF H1 registered for use in meat and poultry plants
- Nonstaining, Odorless and Tasteless
- Water resistant
- Prevents rust and corrosion
- Reduces torque
- Aids assembly/disassembly
- High Temperature protection up to 1800°F
- Contains no metals

APPLICATIONS

Bottling Machinery	Nuts, Bolts, Screws
Pump Gears, Motors	Chain Drives
Packaging Machinery	Stainless Steel Fittings
Conveyor & Oven Bearings	Pipe Fittings
Valve Assemblies	Gaskets
Press Fit Assemblies	Worm Gears

SERVICE RATING: -65°F (-54°C) to 1800°F (982°C)

CONFORMS TO: Military Spec. MIL-PFR-907F

NSF Registered, Category Code: H1 Reg. #048235

For use in Federally Inspected Meat and Poultry Plants

Conforms to FDA Regulation CFR 21, Part 178.3570, Incidental Food Contact.

Note: Not for use on Oxygen services.

PRODUCT CHARACTERISTICS

Thickener	Aluminum Complex
Fluid Type	White Oil & Synthetic
Color/Appearance	White Paste
Dropping Point (ASTM D-566)	450°F (232°C)
Specific Gravity	1.17
Density (lb. /gal)	9.80 Typical
Oil Separation, Wt. % Loss @ 212°F (100°C)	>3.0
Flash Point (ASTM D-92)	>400°F (204°C)
K-Factor*	.15
Carbon Steel Alloy @ 60,000 PSI Contact Stress NLGI Grade	1½
Penetration @ 77°F (ASTM D-217)	290 - 330
Copper Strip Corrosion (ASTM D-4048)	1A
4-Ball (ASTM D-2596)	
Weld Point, kgf	400
Load Wear Index	72
Salt Fog Resistance 20% NaCl at 100°F (ASTM B-117)	+200 hours

*(T = K x D x F) where:

T = torque, K = nut factor, sometimes called the friction factor, D = bolt diameter, and F = bolt tension generated during tightening.

LIMITED WARRANTY

For warranty information please visit

http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com Or write to the Sales Department at the address below.

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318

•An ISO 9001 registered company • www.jetlube.com