

CB-2™

MULTI-PURPOSE GREASE

DESCRIPTION

CB-2™ is an all-purpose, high temperature, lithium 12-hydroxystearate soap grease. Its buttery consistency makes it highly adhesive to metal and it has exceptional mechanical stability. CB-2 is standard in a NLGI 2 grade grease that will accommodate nearly all requirements for a "multipurpose" grease type lubricant. It is also available in other NLGI grades making CB-2 a truly versatile product.

CB-2 has exceptional resistance to the effects of heat, water, oxidation and heavy loadings. It is water resistant, has a dropping point of 390°F (199°C) and contains corrosion and oxidation inhibitors. CB-2 offers protection wherever dirt, dust, high humidity, rain and adverse temperatures are critical problems. It is an all-weather product that lubricates efficiently at temperatures as low as 0°F (-18°C) to 300°F (149°C). For lower temperatures, JET-LUBE's ARCTIC™ is recommended.

CB-2 can be used as a chassis grease for automobiles, trucks, forklifts, or all mobile machinery. Use also on springs, universal joints and water pumps.

- Protects against rust and corrosion
- Pumpable
- Highly adhesive to metal
- Resistant to heat, water, oxidation & heavy loading
- High film strength
- Color—Amber to Brown
- Available in other NLGI grades

APPLICATIONS

CB-2 is specifically formulated for use on fast running bearings, anti-friction bearings, journals and all general greasing where a single, multipurpose product is desired for economy, simplification of inventory and greasing equipment. CB-2 may be used on fans, blowers, pumps, conveyor bearings, drive trains, ball bearings, journal bearings, roller bearings, screw jacks, universal joints and all other lubrication points having sliding or rolling friction that requires a multipurpose grease. This product may be used on oil drilling rigs, on construction and road building equipment, in mining and ship building activities, or wherever an exceptionally high-quality lubricant is indicated.

PRODUCT CHARACTERISTICS

Thickener	Lithium 12-hydroxy Fluid
Type	Petroleum Oil
Color	Amber to Brown
Dropping Point (ASTM D-566)	390°F (199°C)
Specific Gravity	0.90
Density (lb/gal)	7.50
Additive Type	Organic EP,AW,R&O
Flash Point (ASTM D-92)	>430°F (221°C)
Autoignition Point (CALCULATED)	>500°F (260°C)
NLGI Grade	1
Approx. Safe DN Limit	300,000
Penetration @77°F (ASTM D-217)	310 - 340
Copper Strip Corrosion (ASTM D-4048)	1A
4-Ball (ASTM D-2596)	
Weld Point, kgf	200
Load Wear Index	25
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hours	<5
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	100-160
VOC	0 g/L

PACKAGING

Code No.	Container Size	Container
31250	14 oz.	Cartridge
31205	1 lb.	Can
31206	5 lb.	Can
31216	35 lb.	Pail
31224	120 lb.	Drum
31229	400 lb.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

1211



Maidenhead, England

CORPORATE LOCATIONS

Houston, Texas—World Headquarters



Edmonton, Canada



JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com