

# TEMP-GUARD™

## SYNTHETIC HIGH-TEMPERATURE GREASE

### DESCRIPTION

TEMP-GUARD™ is a high quality synthetic grease for high-temperature applications. It contains both graphite and molybdenum disulfide to give the product both low-friction and extreme-pressure capabilities. The synthetic fluid in this product provides exceptional low-temperature flow characteristics as well as high-temperature stability. Its inherent oxidation resistance is further enhanced with high-temperature carbon controlling antioxidants. There are no polymers to build viscosity or viscosity index. This unique feature results in a reduced tendency to coke or form varnish deposits in high temperature applications.

TEMP-GUARD contains no organometallic additives that would decompose at elevated temperatures reducing the lubricative characteristics of the product. The excellent friction and wear properties are a result of a carefully balanced package of the synthetic lubricant, molybdenum disulfide, and graphite.

- Synthetic oils and additives
- High flash point
- Excellent low temperature properties
- Nonmelting
- High film strength with low coefficient of friction
- Low volatility for less smoke and odors
- Color-Black

### APPLICATIONS

- Plain and anti-friction ball and roller bearings
- Kiln bearings
- Crushers
- Crane ladles
- Press and hammer guides
- High temperature blowers, fans and oven conveyors

FOR APPLICATIONS: -10°F (-23°C) to 600°F (204°C)

### PRODUCT CHARACTERISTICS

Thickener	Non Soap
Fluid Type	PAO & Synthetic Ester
Color/Appearance	Black Smooth Grease
Dropping Point (ASTM D-566)	None
Specific Gravity	1.00
Density (lb/gal)	8.3
Additive Type	Graphite & MoS <sub>2</sub>
Flash Point (ASTM D-92)	>600°F (316°C)
Autoignition Point (CALCULATED)	>680°F (360°C)
NLGI Grade	1½
Penetration @77°F (ASTM D-217)	285 - 315
Copper Strip Corrosion (ASTM D-4048)	1A
4-Ball (ASTM D-2596)	
Weld Point, kgf	400
Load Wear Index	50
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hours	<10
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	100 - 150

### PACKAGING

Code No.	Container	Size Container
31850	14 oz.	Cartridge
31805	1 lb.	Can
31806	5 lb.	Can
31816	35 lb.	5 Gal. Pail
31824	120 lb.	15 Gal. Drum

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

0311

## CORPORATE LOCATIONS

Houston, Texas-World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.  
4849 HOMESTEAD RD.,  
SUITE 232  
HOUSTON, TX 77028

WATS: 800-538-5823  
PHONE: 713-670-5700  
FAX: 713-678-4604  
sales@jetlube.com  
www.jetlube.com